

	KP 12	KP 20	KP 30	KP 50	KP 100	KP 150	KP 200
Overall machine dim.s (inch.-mm)							
Width	47.28 (1200)	47.28 (1200)	47.28 (1200)	69 (1750)	75 (1900)	75 (1900)	85 (1900)
Depth	47.28 (1200)	47.28 (1200)	47.28 (1200)	69 (1750)	85 (2150)	85 (2150)	85 (2150)
Height	66.98 (1700)	66.98 (1700)	66.98 (1700)	103 (2600)	103 (2600)	103 (2600)	103 (2600)
Load size (inch.- mm)							
Length	3.94 (100)	11.20 (280)	11.20 (280)	17.72 (450)	23.62 (600)	35.43 (900)	47.24 (1200)
Width	7.88 (200)	9.16 (230)	9.16 (230)	11.81 (300)	17.72 (450)	17.72 (450)	17.72 (450)
Height	2.36 (60)	6.12 (153)	6.12 (153)	7.87 (200)	7.87 (200)	7.87 (200)	7.87 (200)
Batch weight (Kg)	12	20	30	50	100	150	200
Cycles/hour	Up to 10, Depending on cleaning process	Up to 10, Depending on cleaning process	Up to 10, Depending on cleaning process	Up to 10, Depending on cleaning process	Up to 10, Depending on cleaning process	Up to 8, Depending on cleaning process	Up to 8, Depending on cleaning process
External Water Chiller	no	no	no	yes	yes	yes	yes
Power requirements							
Standard system	3x480 V / 60 Hz	3x480 V / 60 Hz	3x480 V / 60 Hz	3x480 V / 60 Hz	3x480 V / 60 Hz	3x480 V / 60 Hz	3x480 V / 60 Hz
KVA (***)	8	10	13	40	47	53	65

*** machine + waste separator, without ultrasonic group, without chiller,